

## Avery Dennison<sup>®</sup> Application Film 831

### Description:

Carrier : Polypropylene film, transparent  
Adhesive : Synthetic rubber

### Features:

- High clarity for accurate registration
- Stick-to-liner properties
- High dimensional stability
- Tear possible, snap to tear the film

### Recommendations for use:

- Transfer of graphics and signs where more support is required
- Multicolour overlays needing accurate registration

### Special note :

- Recommended application tape for Avery Dennison 700 PF, Avery Dennison 800 PC, Avery Dennison 900 SC, Avery Dennison SignFlex 2200 and Avery Dennison SignMask.

## **Technical Information**

- Additional information can be found in technical bulletin 3.13 : Application recommendations for Avery Dennison Application Papers and Avery Dennison Application Film

## PRODUCT CHARACTERISTICS

**Avery Dennison®**  
**AF 831**

Carrier material (paper)	PP-film
Colour	Transparent
Caliper (micron) ISO 538	100
Adhesive tack level	medium

---

### Temperature Range (°C)

Application Temperature	+ 10 °C
Service Temperature	+ 10 °C to + 40 °C

### General:

Shelf life	Stored at 22 °C/ 50-55% RH	2 years
------------	----------------------------	---------

---

### Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

### Warranty

Avery Dennison® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All Avery Dennison® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

### Test methods

More information about our test methods can be found on our website.